

Weather Shield Premium Series[™] Aluminum Clad Wood Windows & Doors

PREMIUM SERIES - CENTER HINGED FRENCH DOOR 3-PANEL (HINGE CODE E) (8510)

SCALE: ELECTRONIC FILE IS FULL SCALE INTRODUCED 1/13 LAST UPDATE 2/15/13

- WEATHER SHIELD RESERVES THE RIGHT, AS NECESSARY, TO CHANGE PRODUCT SPECIFICATIONS AND MATERIALS WITHOUT NOTICE. DIMENSIONS MAY BE ROUNDED TO THE NEAREST 1/16" [2mm].
- IMPORTANT: DIMENSIONS SHOWN ARE FOR STANDARD SHIM SPACE BETWEEN JAMB AND ROUGH OPENING WHEN INSTALLING IN A JURISDICTION REQUIRING DESIGN PRESSURE (DP) RATED PERFORMANCE, WINDOW AND DOOR PRODUCTS MUST BE INSTALLED IN THE SAME METHOD THEY WERE INSTALLED FOR TESTING. A SHIM SPACE, NOT TO EXCEED 1/4" [6mm] IS REQUIRED AROUND THE SIDE JAMBS AND HEAD OF UNITS. REFER TO INSTALLATION INSTRUCTIONS FOR COMPLETE DETAILS.
- FRENCH DOORS WITH THREE-POINT LOCK SYSTEM ARE MANUFACTURED WITH A SHOOTBOLT AND SHOOTBOLT GROMMET AT HEAD (SHOWN) WHICH PROTRUEDS THROUGH THE HEAD INTO ROUGH OPENING APPROXIMATELY 7/16" [11mm]
 7-1/2" [191mm] BOTTOM RAIL HEIGHT IS STANDARD ON ALL DOORS UP TO 8-2 CALL-OUT HEIGHT
- 10" [254mm] BOTTOM RAIL HEIGHT IS STANDARD ON ALL DOROS OVER 8-2 CALL-OUT HEIGHT
- 10" [254mm] AND 12" [305mm] BOTTOM RAIL HEIGHTS ARE AVAILABLE AS AN OPTION ON ALL DOORS

