

Signature Series®

**Aluminum Clad Wood Windows & Doors** 

SIGNATURE SERIES - OUTSWING HINGED DOOR DIRECT-SET TRANSOM (830)


SCALE: ELECTRONIC FILE IS FULL SCALE INTRODUCED 7/12 LAST UPDATE 1/30/13


- WEATHER SHIELD RESERVES THE RIGHT, AS NECESSARY, TO CHANGE PRODUCT SPECIFICATIONS AND MATERIALS WITHOUT NOTICE.
- DIMENSIONS MAY BE ROUNDED TO THE NEAREST 1/16" [2mm].
- IMPORTANT: DIMENSIONS SHOWN ARE FOR STANDARD SHIM SPACE BETWEEN JAMB AND ROUGH OPENING. WHEN INSTALLING IN A JURISDICTION REQUIRING DESIGN PRESSURE (DP) RATED PERFORMANCE, WINDOW AND DOOR PRODUCTS MUST BE INSTALLED IN THE SAME METHOD THEY WERE INSTALLED FOR TESTING. A SHIM SPACE, NOT TO EXCEED 14/4" (BMM) IS REQUIRED AROUND THE SIDE JAMBS AND HEAD OF UNITS. REFER TO INSTALLATION INSTRUCTIONS FOR COMPLETE DETAILS.
- (a) HINGED DOOR DIRECT-SET TRANSOM (830) OVER OUTSWING HINGED DOOR (8610)


  \*SINGLE TRANSOMS OVER 24-1/2" [622mm] R.O. HEIGHT REQUIRE MINIMUM 3-1/2" [89mm] HORIZONTAL SPREAD

  \*TWO-WIDE AND THREE-WIDE TRANSOMS REQUIRE MINIMUM 3-1/2" [89mm] HORIZONTAL SPREAD


  \*SINGLE TRANSOM OVER 3-PANEL DOORS REQUIRE MINIMUM 3-1/2" [89mm] HORIZONTAL SPREAD









**B - HORIZONTAL SECTION** 



C - HORIZONTAL TIGHT STACK SECTION (a)



C - HORIZONTAL 3-1/2" [89mm] STACK SECTION (a)



**D - VERTICAL TIGHT MULL SECTION**