



ProShield®

Premium Vinyl Clad Windows & Doors

Performance Data & Information

Home Energy Efficiency Improvement Tax Credit

Manufacturer's Certification Statement

One Weather Shield Plaza, Medford, WI 54451

Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

ProShield Vinyl Clad Products

<u>Product Line</u>	<u>Grills</u>	<u>Glazing Thickness</u>	<u>Glazing Option</u>	<u>U-Factor</u>	<u>SHGC</u>	<u>Tax Credit</u>
Pro-Tilt	none	5/8"	Insul Low-e w/ Argon	0.29	0.30	Y
Pro-Tilt	none	5/8"	Insul Bronze Low-e w/ Argon	0.30	0.29	Y
Pro-Tilt	none	5/8"	Insul Low-e 240 w/ Argon	0.30	0.19	Y
Pro-Tilt	none	5/8"	Zo-e-shield 5 w/ Argon	0.29	0.20	Y
Pro-Tilt	Std GIA/SDL	5/8"	Insul Low-e w/ Argon	0.30	0.27	Y
Pro-Tilt	Std GIA/SDL	5/8"	Zo-e-shield 5 w/ Argon	0.30	0.18	Y
Slider	none	5/8"	Insul Low-e w/ Argon	0.29	0.30	Y
Slider	none	5/8"	Insul Bronze Low-e w/ Argon	0.29	0.29	Y
Slider	none	5/8"	Insul Low-e 240 w/ Argon	0.29	0.19	Y
Slider	none	5/8"	Zo-e-shield 5 w/ Argon	0.28	0.20	Y
Slider	Std GIA/SDL	5/8"	Insul Low-e w/ Argon	0.30	0.27	Y
Slider	Std GIA/SDL	5/8"	Insul Bronze Low-e w/ Argon	0.30	0.26	Y
Slider	Std GIA/SDL	5/8"	Insul Low-e 240 w/ Argon	0.30	0.17	Y
Slider	Std GIA/SDL	5/8"	Zo-e-shield 5 w/ Argon	0.29	0.18	Y
Slider	15/16" GIA	5/8"	Insul Low-e w/ Argon	0.30	0.24	Y
Slider	15/16" GIA	5/8"	Insul Bronze Low-e w/ Argon	0.30	0.23	Y
Slider	15/16" GIA	5/8"	Insul Low-e 240 w/ Argon	0.30	0.15	Y
Slider	15/16" GIA	5/8"	Zo-e-shield 5 w/ Argon	0.29	0.16	Y
Direct Set	none	13/16"	Insul Low-e 240 w/ Argon	0.27	0.22	Y
Direct Set	none	13/16"	Zo-e-shield 5	0.30	0.24	Y
Direct Set	none	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.24	Y
Direct Set	Std GIA/SDL	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.27	Y
Direct Set	Std GIA/SDL	13/16"	Insul Low-e 240 w/ Argon	0.27	0.20	Y
Direct Set	Std GIA/SDL	13/16"	Zo-e-shield 5	0.30	0.22	Y
Direct Set	Std GIA/SDL	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.22	Y
Direct Set	15/16" GIA	13/16"	Insul Low-e w/ Argon	0.27	0.29	Y
Direct Set	15/16" GIA	13/16"	Insul Low-e 240 w/ Argon	0.27	0.18	Y
Direct Set	15/16" GIA	13/16"	Zo-e-shield 5	0.30	0.20	Y
Direct Set	15/16" GIA	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.20	Y
Direct Set	none	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.25	Y
Direct Set	none	13/16"	Zo-e-shield 6 w/ Argon	0.26	0.25	Y
Direct Set	Std GIA/SDL	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.23	Y
Direct Set	Std GIA/SDL	13/16"	Zo-e-shield 6 w/ Argon	0.28	0.23	Y
Direct Set	15/16" GIA	13/16"	Insul Bronze Low-e w/ Argon	0.28	0.29	Y
Direct Set	15/16" GIA	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.21	Y
Direct Set	15/16" GIA	13/16"	Zo-e-shield 6 w/ Argon	0.28	0.21	Y
Casement	none	13/16"	Insul Low-e	0.30	0.30	Y
Casement	none	13/16"	Insul Low-e w/ Argon	0.27	0.30	Y
Casement	none	13/16"	Insul Bronze Low-e	0.30	0.29	Y
Casement	none	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.29	Y
Casement	none	13/16"	Insul Low-e 240 w/ Argon	0.28	0.18	Y
Casement	none	13/16"	Zo-e-shield 5	0.30	0.20	Y
Casement	none	13/16"	Zo-e-shield 5 w/ Argon	0.27	0.20	Y
Casement	none	13/16"	Zo-e-shield 6	0.30	0.20	Y
Casement	none	13/16"	Zo-e-shield 6 w/ Argon	0.27	0.20	Y

Continued on the next page



ProShield®

Premium Vinyl Clad Windows & Doors

Performance Data & Information

Home Energy Efficiency Improvement Tax Credit

Manufacturer's Certification Statement

One Weather Shield Plaza, Medford, WI 54451

Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

ProShield Vinyl Clad Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Casement	Std GIA/SDL	13/16"	Insul Low-e	0.30	0.28	Y
Casement	Std GIA/SDL	13/16"	Insul Low-e w/ Argon	0.27	0.27	Y
Casement	Std GIA/SDL	13/16"	Insul Bronze Low-e	0.30	0.26	Y
Casement	Std GIA/SDL	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.26	Y
Casement	Std GIA/SDL	13/16"	Insul Low-e 240 w/ Argon	0.28	0.17	Y
Casement	Std GIA/SDL	13/16"	Zo-e-shield 5	0.30	0.19	Y
Casement	Std GIA/SDL	13/16"	Zo-e-shield 5 w/ Argon	0.27	0.18	Y
Casement	Std GIA/SDL	13/16"	Zo-e-shield 6	0.30	0.19	Y
Casement	Std GIA/SDL	13/16"	Zo-e-shield 6 w/ Argon	0.27	0.18	Y
Casement	15/16" GIA	13/16"	Insul Low-e	0.30	0.25	Y
Casement	15/16" GIA	13/16"	Insul Low-e w/ Argon	0.27	0.25	Y
Casement	15/16" GIA	13/16"	Insul Bronze Low-e	0.30	0.24	Y
Casement	15/16" GIA	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.24	Y
Casement	15/16" GIA	13/16"	Insul Low-e 240 w/ Argon	0.28	0.15	Y
Casement	15/16" GIA	13/16"	Zo-e-shield 5	0.30	0.17	Y
Casement	15/16" GIA	13/16"	Zo-e-shield 5 w/ Argon	0.27	0.17	Y
Casement	15/16" GIA	13/16"	Zo-e-shield 6	0.30	0.17	Y
Casement	15/16" GIA	13/16"	Zo-e-shield 6 w/ Argon	0.27	0.17	Y
Awning	none	13/16"	Insul Low-e w/ Argon	0.27	0.30	Y
Awning	none	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.29	Y
Awning	none	13/16"	Insul Low-e 240 w/ Argon	0.28	0.18	Y
Awning	none	13/16"	Zo-e-shield 5	0.30	0.20	Y
Awning	none	13/16"	Zo-e-shield 5 w/ Argon	0.27	0.20	Y
Awning	none	13/16"	Zo-e-shield 6	0.30	0.20	Y
Awning	none	13/16"	Zo-e-shield 6 w/ Argon	0.27	0.20	Y
Awning	Std GIA/SDL	13/16"	Insul Low-e w/ Argon	0.27	0.27	Y
Awning	Std GIA/SDL	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.26	Y
Awning	Std GIA/SDL	13/16"	Insul Low-e 240 w/ Argon	0.28	0.17	Y
Awning	Std GIA/SDL	13/16"	Zo-e-shield 5	0.30	0.19	Y
Awning	Std GIA/SDL	13/16"	Zo-e-shield 5 w/ Argon	0.27	0.18	Y
Awning	Std GIA/SDL	13/16"	Zo-e-shield 6	0.30	0.19	Y
Awning	Std GIA/SDL	13/16"	Zo-e-shield 6 w/ Argon	0.27	0.18	Y
Awning	15/16" GIA	13/16"	Insul Low-e w/ Argon	0.27	0.25	Y
Awning	15/16" GIA	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.24	Y
Awning	15/16" GIA	13/16"	Insul Low-e 240 w/ Argon	0.28	0.16	Y
Awning	15/16" GIA	13/16"	Zo-e-shield 5	0.30	0.17	Y
Awning	15/16" GIA	13/16"	Zo-e-shield 5 w/ Argon	0.27	0.17	Y
Awning	15/16" GIA	13/16"	Zo-e-shield 6	0.30	0.17	Y
Awning	15/16" GIA	13/16"	Zo-e-shield 6 w/ Argon	0.27	0.17	Y

Continued on the next page



ProShield®

Premium Vinyl Clad Windows & Doors

Performance Data & Information

Home Energy Efficiency Improvement Tax Credit

Manufacturer's Certification Statement

One Weather Shield Plaza, Medford, WI 54451

Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

ProShield Vinyl Clad Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Casement Picture	none	13/16"	Insul Low-e	0.30	0.30	Y
Casement Picture	none	13/16"	Insul Low-e w/ Argon	0.27	0.30	Y
Casement Picture	none	13/16"	Insul Bronze Low-e	0.30	0.29	Y
Casement Picture	none	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.29	Y
Casement Picture	none	13/16"	Insul Low-e 240 w/ Argon	0.27	0.19	Y
Casement Picture	none	13/16"	Zo-e-shield 5	0.30	0.20	Y
Casement Picture	none	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.20	Y
Casement Picture	none	13/16"	Zo-e-shield 6	0.30	0.20	Y
Casement Picture	none	13/16"	Zo-e-shield 6 w/ Argon	0.26	0.20	Y
Casement Picture	none	13/16"	Zo-e-shield 7	0.28	0.16	Y
Casement Picture	none	13/16"	Zo-e-shield 7 w/ Argon	0.23	0.16	Y
Casement Picture	Std GIA/SDL	13/16"	Insul Low-e	0.30	0.28	Y
Casement Picture	Std GIA/SDL	13/16"	Insul Low-e w/ Argon	0.27	0.27	Y
Casement Picture	Std GIA/SDL	13/16"	Insul Bronze Low-e	0.30	0.26	Y
Casement Picture	Std GIA/SDL	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.26	Y
Casement Picture	Std GIA/SDL	13/16"	Insul Low-e 240 w/ Argon	0.27	0.17	Y
Casement Picture	Std GIA/SDL	13/16"	Zo-e-shield 5	0.30	0.19	Y
Casement Picture	Std GIA/SDL	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.18	Y
Casement Picture	Std GIA/SDL	13/16"	Zo-e-shield 6	0.30	0.19	Y
Casement Picture	Std GIA/SDL	13/16"	Zo-e-shield 6 w/ Argon	0.26	0.18	Y
Casement Picture	15/16" GIA	13/16"	Insul Low-e	0.30	0.25	Y
Casement Picture	15/16" GIA	13/16"	Insul Low-e w/ Argon	0.27	0.25	Y
Casement Picture	15/16" GIA	13/16"	Insul Bronze Low-e	0.30	0.24	Y
Casement Picture	15/16" GIA	13/16"	Insul Bronze Low-e w/ Argon	0.27	0.24	Y
Casement Picture	15/16" GIA	13/16"	Insul Low-e 240 w/ Argon	0.27	0.16	Y
Casement Picture	15/16" GIA	13/16"	Zo-e-shield 5	0.30	0.17	Y
Casement Picture	15/16" GIA	13/16"	Zo-e-shield 5 w/ Argon	0.26	0.17	Y
Casement Picture	15/16" GIA	13/16"	Zo-e-shield 6	0.30	0.17	Y
Casement Picture	15/16" GIA	13/16"	Zo-e-shield 6 w/ Argon	0.26	0.17	Y



ProShield®

Premium Vinyl Clad Windows & Doors

Performance Data & Information

Home Energy Efficiency Improvement Tax Credit

Manufacturer's Certification Statement

One Weather Shield Plaza, Medford, WI 54451

Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

ProShield Vinyl Clad Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Sliding Patio Door	none	3/4"	Insul Low-e 240 w/ Argon	0.30	0.20	Y
Sliding Patio Door	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.30	0.18	Y
Sliding Patio Door	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.30	0.16	Y
Inswing Hinged Door	none	1"	Zo-e-shield 7	0.29	0.15	Y
Inswing Hinged Door	none	1"	Zo-e-shield 7 w/ Argon	0.26	0.14	Y
Inswing Hinged Door	Std GIA/SDL	1"	Zo-e-shield 7	0.29	0.13	Y
Inswing Hinged Door	Std GIA/SDL	1"	Zo-e-shield 7 w/ Argon	0.27	0.13	Y
Inswing Hinged Door	15/16" GIA	1"	Zo-e-shield 7	0.29	0.11	Y
Inswing Hinged Door	15/16" GIA	1"	Zo-e-shield 7 w/ Argon	0.27	0.11	Y
Outswing Hinged Door	none	1"	Zo-e-shield 6 w/ Argon	0.30	0.16	Y
Outswing Hinged Door	none	1"	Zo-e-shield 7	0.28	0.15	Y
Outswing Hinged Door	none	1"	Zo-e-shield 7 w/ Argon	0.26	0.15	Y
Outswing Hinged Door	Std GIA/SDL	1"	Zo-e-shield 6 w/ Argon	0.30	0.14	Y
Outswing Hinged Door	Std GIA/SDL	1"	Zo-e-shield 7	0.29	0.13	Y
Outswing Hinged Door	Std GIA/SDL	1"	Zo-e-shield 7 w/ Argon	0.26	0.13	Y
Outswing Hinged Door	15/16" GIA	1"	Zo-e-shield 6 w/ Argon	0.30	0.12	Y
Outswing Hinged Door	15/16" GIA	1"	Zo-e-shield 7	0.29	0.11	Y
Outswing Hinged Door	15/16" GIA	1"	Zo-e-shield 7 w/ Argon	0.26	0.11	Y

Terms and Conditions:

Updated 06/25/09

Std GIA/SDL refers to 5/8" Grilles in the Airspace, 11/16" Grilles in the Airspace, and Simulated Divided Lite.

15/16" GIA refers to 15/16" Grilles in the Airspace.

All units are tested in accordance to National Fenestration Rating Counsel (NFRC) procedures. U-Factors are derived from computer simulations using WINDOW 5.2 and THERM 5.2 programs. Simulations are then verified by testing in accordance with NFRC 100-04.

The performance of windows and doors may be affected by factors beyond Weather Shield's control, such as handling and installation, construction details of the building, exposure conditions, maintenance, normal wear and tear, migration of an inert gas from the insulated glass unit and the like. Ratings (for example, R or U-factors, infiltration tests, etc.) are for comparison purposes only. While Weather Shield products are manufactured to meet or exceed published ratings, it is not possible to guarantee that they will meet or exceed those ratings after they have been installed, and this is specifically excluded from any warranty.

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

Emory Budzinski

Emory Budzinski
Senior Product Manager