



Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

Aluminum Clad Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Double Hung	none	3/4"	Insul Low-e w/ Argon	0.30	0.19	Y
Double Hung	none	3/4"	Insul Bronze Low-e w/ Krypton	0.30	0.22	Y
Double Hung	none	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.19	Y
Double Hung	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.30	0.18	Y
Double Hung	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Krypton	0.30	0.19	Y
Double Hung	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.18	Y
Double Hung	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.30	0.16	Y
Double Hung	15/16" GIA	3/4"	Insul Bronze Low-e w/ Krypton	0.30	0.17	Y
Double Hung	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.16	Y
DH Transom	none	1"	Insul Bronze Low-e w/ Argon	0.29	0.26	Y
DH Transom	none	1"	Insul Low-e 240 w/ Argon	0.29	0.19	Y
DH Transom	none	1"	Zo-e-shield 5 w/ Argon	0.28	0.21	Y
DH Transom	none	1"	Zo-e-shield 6 w/ Argon	0.28	0.21	Y
DH Transom	none	1"	Zo-e-shield 7	0.28	0.20	Y
DH Transom	none	1"	Zo-e-shield 7 w/ Argon	0.24	0.20	Y
DH Transom	Std GIA/SDL	1"	Insul Low-e w/ Argon	0.29	0.28	Y
DH Transom	Std GIA/SDL	1"	Insul Bronze Low-e w/ Argon	0.29	0.23	Y
DH Transom	Std GIA/SDL	1"	Insul Low-e 240 w/ Argon	0.29	0.17	Y
DH Transom	Std GIA/SDL	1"	Zo-e-shield 5 w/ Argon	0.28	0.19	Y
DH Transom	Std GIA/SDL	1"	Zo-e-shield 6 w/ Argon	0.28	0.19	Y
DH Transom	15/16" GIA	1"	Insul Low-e w/ Argon	0.29	0.25	Y
DH Transom	15/16" GIA	1"	Insul Bronze Low-e w/ Argon	0.29	0.21	Y
DH Transom	15/16" GIA	1"	Insul Low-e 240 w/ Argon	0.29	0.16	Y
DH Transom	15/16" GIA	1"	Zo-e-shield 5 w/ Argon	0.28	0.18	Y
DH Transom	15/16" GIA	1"	Zo-e-shield 6 w/ Argon	0.28	0.17	Y
DH Picture	none	1"	Insul Low-e w/ Argon	0.29	0.30	Y
DH Picture	none	1"	Insul Bronze Low-e w/ Argon	0.29	0.24	Y
DH Picture	none	1"	Insul Low-e 240 w/ Argon	0.29	0.18	Y
DH Picture	none	1"	Zo-e-shield 5 w/ Argon	0.28	0.20	Y
DH Picture	none	1"	Zo-e-shield 6 w/ Argon	0.28	0.20	Y
DH Picture	none	1"	Zo-e-shield 7	0.26	0.19	Y
DH Picture	none	1"	Zo-e-shield 7 w/ Argon	0.23	0.19	Y
DH Picture	Std GIA/SDL	1"	Insul Low-e w/ Argon	0.29	0.27	Y
DH Picture	Std GIA/SDL	1"	Insul Bronze Low-e w/ Argon	0.29	0.22	Y
DH Picture	Std GIA/SDL	1"	Insul Low-e 240 w/ Argon	0.29	0.16	Y
DH Picture	Std GIA/SDL	1"	Zo-e-shield 5 w/ Argon	0.28	0.18	Y
DH Picture	Std GIA/SDL	1"	Zo-e-shield 6 w/ Argon	0.28	0.18	Y
DH Picture	15/16" GIA	1"	Insul Low-e w/ Argon	0.29	0.24	Y
DH Picture	15/16" GIA	1"	Insul Bronze Low-e w/ Argon	0.29	0.20	Y
DH Picture	15/16" GIA	1"	Insul Low-e 240 w/ Argon	0.29	0.15	Y
DH Picture	15/16" GIA	1"	Zo-e-shield 5 w/ Argon	0.28	0.17	Y
DH Picture	15/16" GIA	1"	Zo-e-shield 6 w/ Argon	0.28	0.16	Y
Slider	none	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.21	Y
Slider	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.19	Y
Slider	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.17	Y



Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

Aluminum Clad Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Direct Set	none	1"	Insul Low-e 240 w/ Argon	0.29	0.23	Y
Direct Set	none	1"	Zo-e-shield 5 w/ Argon	0.28	0.24	Y
Direct Set	none	1"	Zo-e-shield 6 w/ Argon	0.28	0.25	Y
Direct Set	none	1"	Zo-e-shield 7	0.24	0.23	Y
Direct Set	none	1"	Zo-e-shield 7 w/ Argon	0.20	0.23	Y
Direct Set	Std GIA/SDL	1"	Insul Low-e 240 w/ Argon	0.29	0.21	Y
Direct Set	Std GIA/SDL	1"	Insul Gray Low-e w/ Argon	0.28	0.30	Y
Direct Set	Std GIA/SDL	1"	Zo-e-shield 5 w/ Argon	0.28	0.22	Y
Direct Set	Std GIA/SDL	1"	Zo-e-shield 6 w/ Argon	0.28	0.22	Y
Casement	none	3/4"	Insul Low-e w/ Argon	0.30	0.30	Y
Casement	none	3/4"	Insul Bronze Low-e w/ Argon	0.30	0.29	Y
Casement	none	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.20	Y
Casement	none	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.20	Y
Casement	none	7/8"	Zo-e-shield 7	0.30	0.19	Y
Casement	none	7/8"	Zo-e-shield 7 w/ Argon	0.26	0.19	Y
Casement	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.30	0.28	Y
Casement	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.30	0.26	Y
Casement	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.18	Y
Casement	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.30	0.24	Y
Casement	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.30	0.24	Y
Casement	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.17	Y
Awning	none	3/4"	Insul Low-e w/ Argon	0.30	0.30	Y
Awning	none	3/4"	Insul Bronze Low-e w/ Argon	0.30	0.29	Y
Awning	none	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.20	Y
Awning	none	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.20	Y
Awning	none	7/8"	Zo-e-shield 7	0.30	0.19	Y
Awning	none	7/8"	Zo-e-shield 7 w/ Argon	0.26	0.19	Y
Awning	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.30	0.28	Y
Awning	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.30	0.26	Y
Awning	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.19	Y
Awning	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.30	0.25	Y
Awning	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.30	0.24	Y
Awning	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.17	Y
Casement Picture	none	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.23	Y
Casement Picture	none	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.23	Y
Casement Picture	none	7/8"	Zo-e-shield 7	0.28	0.21	Y
Casement Picture	none	7/8"	Zo-e-shield 7 w/ Argon	0.24	0.21	Y
Casement Picture	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.28	0.29	Y
Casement Picture	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.21	Y
Casement Picture	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.20	Y
Casement Picture	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.28	0.28	Y
Casement Picture	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.28	0.26	Y
Casement Picture	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.19	Y
Casement Picture	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.19	Y
French Casement	none	3/4"	Insul Low-e w/ Krypton	0.30	0.30	Y
French Casement	Std GIA/SDL	3/4"	Insul Low-e w/ Krypton	0.30	0.27	Y



Weather Shield®

Premium Wood & Aluminum Clad Windows & Doors

Performance Data & Information

Home Energy Efficiency Improvement Tax Credit

Manufacturer's Certification Statement

One Weather Shield Plaza, Medford, WI 54451

Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

Aluminum Clad Products

Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Sliding Patio Door	none	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.21	Y
Sliding Patio Door	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.19	Y
Sliding Patio Door	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.30	0.17	Y
2.25 FD Inswing*	none	1"	Zo-e-shield 5 w/ Argon	0.30	0.15	Y
2.25 FD Inswing*	none	1"	Zo-e-shield 6 w/ Argon	0.29	0.15	Y
2.25 FD Inswing*	none	1"	Zo-e-shield 7	0.29	0.14	Y
2.25 FD Inswing*	none	1"	Zo-e-shield 7 w/ Argon	0.26	0.14	Y
2.25 FD Inswing*	Std GIA/SDL	1"	Zo-e-shield 5 w/ Argon	0.30	0.13	Y
2.25 FD Inswing*	Std GIA/SDL	1"	Zo-e-shield 6 w/ Argon	0.29	0.13	Y
2.25 FD Inswing*	15/16" GIA	1"	Zo-e-shield 5 w/ Argon	0.30	0.12	Y
2.25 FD Inswing*	15/16" GIA	1"	Zo-e-shield 6 w/ Argon	0.29	0.11	Y
2.25 FD Outswing*	none	1"	Zo-e-shield 6 w/ Argon	0.30	0.15	Y
2.25 FD Outswing*	none	1"	Zo-e-shield 7	0.30	0.14	Y
2.25 FD Outswing*	none	1"	Zo-e-shield 7 w/ Argon	0.27	0.14	Y
2.25 FD Outswing*	Std GIA/SDL	1"	Zo-e-shield 6 w/ Argon	0.30	0.13	Y
2.25 FD Outswing*	15/16" GIA	1"	Zo-e-shield 6 w/ Argon	0.30	0.12	Y

Terms and Conditions:

*Ordered as Legacy Series 2-1/4" Doors

Updated 06/25/09

Std GIA/SDL refers to 5/8" Grilles in the Airspace, 11/16" Grilles in the Airspace, and Simulated Divided Lite.

15/16" GIA refers to 15/16" Grilles in the Airspace.

All units are tested in accordance to National Fenestration Rating Counsel (NFRC) procedures. U-Factors are derived from computer simulations using WINDOW 5.2 and THERM 5.2 programs. Simulations are then verified by testing in accordance with NFRC 100-04.

The performance of windows and doors may be affected by factors beyond Weather Shield's control, such as handling and installation, construction details of the building, exposure conditions, maintenance, normal wear and tear, migration of an inert gas from the insulated glass unit and the like. Ratings (for example, R or U-factors, infiltration tests, etc.) are for comparison purposes only. While Weather Shield products are manufactured to meet or exceed published ratings, it is not possible to guarantee that they will meet or exceed those ratings after they have been installed, and this is specifically excluded from any warranty.

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

Emory Budzinski

Emory Budzinski
Senior Product Manager