



Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

Primed Exterior Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Double Hung	none	3/4"	Insul Low-e w/ Argon	0.29	0.29	Y
Double Hung	none	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.27	Y
Double Hung	none	3/4"	Insul Low-e 240 w/ Argon	0.30	0.18	Y
Double Hung	none	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.19	Y
Double Hung	none	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.19	Y
Double Hung	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.29	0.26	Y
Double Hung	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.25	Y
Double Hung	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.30	0.16	Y
Double Hung	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.17	Y
Double Hung	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.29	0.23	Y
Double Hung	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.22	Y
Double Hung	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.30	0.14	Y
Double Hung	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.15	Y
DH Picture	none	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.20	Y
DH Picture	none	1"	Insul Low-e w/ Argon	0.28	0.29	Y
DH Picture	none	1"	Insul Bronze Low-e w/ Argon	0.28	0.24	Y
DH Picture	none	1"	Insul Low-e 240 w/ Argon	0.28	0.18	Y
DH Picture	none	1"	Zo-e-shield 5	0.30	0.21	Y
DH Picture	none	1"	Zo-e-shield 5 w/ Argon	0.27	0.20	Y
DH Picture	none	1"	Zo-e-shield 6 w/ Argon	0.27	0.20	Y
DH Picture	none	1"	Zo-e-shield 7	0.27	0.19	Y
DH Picture	none	1"	Zo-e-shield 7 w/ Argon	0.23	0.19	Y
DH Picture	Std GIA/SDL	1"	Insul Low-e w/ Argon	0.28	0.26	Y
DH Picture	Std GIA/SDL	1"	Insul Bronze Low-e w/ Argon	0.28	0.22	Y
DH Picture	Std GIA/SDL	1"	Insul Low-e 240 w/ Argon	0.28	0.16	Y
DH Picture	Std GIA/SDL	1"	Zo-e-shield 5	0.30	0.19	Y
DH Picture	Std GIA/SDL	1"	Zo-e-shield 5 w/ Argon	0.27	0.18	Y
DH Picture	Std GIA/SDL	1"	Zo-e-shield 6 w/ Argon	0.27	0.18	Y
DH Picture	15/16" GIA	1"	Insul Low-e w/ Argon	0.28	0.24	Y
DH Picture	15/16" GIA	1"	Insul Bronze Low-e w/ Argon	0.28	0.19	Y
DH Picture	15/16" GIA	1"	Insul Low-e 240 w/ Argon	0.28	0.15	Y
DH Picture	15/16" GIA	1"	Zo-e-shield 5	0.30	0.17	Y
DH Picture	15/16" GIA	1"	Zo-e-shield 5 w/ Argon	0.27	0.16	Y
DH Picture	15/16" GIA	1"	Zo-e-shield 6 w/ Argon	0.27	0.16	Y
Direct Set	none	1"	Insul Low-e 240 w/ Argon	0.27	0.21	Y
Direct Set	none	1"	Insul Bronze Low-e	0.30	0.29	Y
Direct Set	none	1"	Insul Bronze Low-e w/ Argon	0.27	0.29	Y
Direct Set	none	1"	Insul Gray Low-e	0.30	0.26	Y
Direct Set	none	1"	Insul Gray Low-e w/ Argon	0.27	0.26	Y
Direct Set	Std GIA/SDL	1"	Insul Low-e 240 w/ Argon	0.27	0.20	Y
Direct Set	Std GIA/SDL	1"	Insul Bronze Low-e	0.30	0.27	Y
Direct Set	Std GIA/SDL	1"	Insul Bronze Low-e w/ Argon	0.27	0.26	Y
Direct Set	Std GIA/SDL	1"	Insul Gray Low-e	0.30	0.24	Y
Direct Set	Std GIA/SDL	1"	Insul Gray Low-e w/ Argon	0.27	0.23	Y



Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

Primed Exterior Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Slider	none	3/4"	Insul Low-e 240 w/ Argon	0.29	0.19	Y
Slider	none	3/4"	Insul Bronze Low-e w/ Argon	0.30	0.29	Y
Slider	none	3/4"	Insul Gray Low-e w/ Argon	0.30	0.28	Y
Slider	none	3/4"	Zo-e-shield 5 w/ Argon	0.29	0.20	Y
Slider	none	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.20	Y
Slider	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.30	0.28	Y
Slider	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.29	0.17	Y
Slider	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.30	0.26	Y
Slider	Std GIA/SDL	3/4"	Insul Gray Low-e	0.30	0.24	Y
Slider	Std GIA/SDL	3/4"	Insul Gray Low-e w/ Argon	0.30	0.25	Y
Slider	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.28	0.18	Y
Slider	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.18	Y
Casement	none	3/4"	Insul Low-e w/ Argon	0.29	0.30	Y
Casement	none	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.28	Y
Casement	none	3/4"	Insul Low-e 240 w/ Argon	0.29	0.18	Y
Casement	none	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.20	Y
Casement	none	3/4"	Zo-e-shield 6 w/ Argon	0.28	0.20	Y
Casement	none	7/8"	Zo-e-shield 7	0.28	0.18	Y
Casement	none	7/8"	Zo-e-shield 7 w/ Argon	0.24	0.18	Y
Casement	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.29	0.27	Y
Casement	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.26	Y
Casement	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.29	0.17	Y
Casement	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.18	Y
Casement	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.18	Y
Casement	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.29	0.25	Y
Casement	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.23	Y
Casement	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.29	0.15	Y
Casement	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.16	Y
Casement	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.16	Y
Awning	none	3/4"	Insul Low-e w/ Argon	0.29	0.29	Y
Awning	none	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.27	Y
Awning	none	3/4"	Insul Low-e 240 w/ Argon	0.29	0.18	Y
Awning	none	3/4"	Zo-e-shield 5	0.30	0.19	Y
Awning	none	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.19	Y
Awning	none	3/4"	Zo-e-shield 6 w/ Argon	0.28	0.19	Y
Awning	none	7/8"	Zo-e-shield 7	0.28	0.18	Y
Awning	none	7/8"	Zo-e-shield 7 w/ Argon	0.24	0.18	Y
Awning	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.29	0.26	Y
Awning	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.25	Y
Awning	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.29	0.16	Y
Awning	Std GIA/SDL	3/4"	Zo-e-shield 5	0.30	0.18	Y
Awning	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.18	Y
Awning	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.18	Y



Weather Shield®

Premium Wood & Aluminum Clad Windows & Doors

Performance Data & Information

Home Energy Efficiency Improvement Tax Credit

Manufacturer's Certification Statement

One Weather Shield Plaza, Medford, WI 54451

Weather Shield Windows and Doors is a manufacturer of exterior windows, patio doors and entrance doors. This Manufacturer's Certification Statement serves as verification that the Weather Shield window and door products listed below qualify for the Energy Tax Credit in accordance with IRS 2006-26 document.

Primed Exterior Products						
Product Line	Grills	Glazing Thickness	Glazing Option	U-Factor	SHGC	Tax Credit
Awning	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.29	0.24	Y
Awning	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.29	0.23	Y
Awning	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.29	0.15	Y
Awning	15/16" GIA	3/4"	Zo-e-shield 5	0.30	0.16	Y
Awning	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.16	Y
Awning	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.29	0.16	Y
Casement Pict.	none	3/4"	Insul Low-e 240 w/ Argon	0.28	0.20	Y
Casement Pict.	none	3/4"	Zo-e-shield 5	0.30	0.23	Y
Casement Pict.	none	3/4"	Zo-e-shield 5 w/ Argon	0.26	0.22	Y
Casement Pict.	none	3/4"	Zo-e-shield 6 w/ Argon	0.28	0.22	Y
Casement Pict.	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.28	0.30	Y
Casement Pict.	Std GIA/SDL	3/4"	Insul Bronze Low-e w/ Argon	0.28	0.29	Y
Casement Pict.	Std GIA/SDL	3/4"	Insul Low-e 240 w/ Argon	0.28	0.19	Y
Casement Pict.	Std GIA/SDL	3/4"	Zo-e-shield 5	0.30	0.18	Y
Casement Pict.	Std GIA/SDL	3/4"	Zo-e-shield 5 w/ Argon	0.27	0.18	Y
Casement Pict.	Std GIA/SDL	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.20	Y
Casement Pict.	15/16" GIA	3/4"	Insul Low-e w/ Argon	0.28	0.27	Y
Casement Pict.	15/16" GIA	3/4"	Insul Bronze Low-e w/ Argon	0.28	0.26	Y
Casement Pict.	15/16" GIA	3/4"	Insul Low-e 240 w/ Argon	0.28	0.17	Y
Casement Pict.	15/16" GIA	3/4"	Zo-e-shield 5	0.30	0.18	Y
Casement Pict.	15/16" GIA	3/4"	Zo-e-shield 5 w/ Argon	0.26	0.18	Y
Casement Pict.	15/16" GIA	3/4"	Zo-e-shield 6 w/ Argon	0.30	0.18	Y
Sld Patio Door	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.30	0.28	Y
Fr. Sld Patio Dr	none	3/4"	Insul Low-e w/ Argon	0.30	0.26	Y
Fr. Sld Patio Dr	Std GIA/SDL	3/4"	Insul Low-e w/ Argon	0.30	0.23	Y

Terms and Conditions:

Updated 03/30/09

Std GIA/SDL refers to 5/8" Grilles in the Airspace, 11/16" Grilles in the Airspace, and Simulated Divided Lite.

15/16" GIA refers to 15/16" Grilles in the Airspace.

All units are tested in accordance to National Fenestration Rating Counsel (NFRC) procedures. U-Factors are derived from computer simulations using WINDOW 5.2 and THERM 5.2 programs. Simulations are then verified by testing in accordance with NFRC 100-04.

The performance of windows and doors may be affected by factors beyond Weather Shield's control, such as handling and installation, construction details of the building, exposure conditions, maintenance, normal wear and tear, migration of an inert gas from the insulated glass unit and the like. Ratings (for example, R or U-factors, infiltration tests, etc.) are for comparison purposes only. While Weather Shield products are manufactured to meet or exceed published ratings, it is not possible to guarantee that they will meet or exceed those ratings after they have been installed, and this is specifically excluded from any warranty.

Under penalties of perjury, I declare that I have examined this certification statement, and to the best of my knowledge and belief, the facts are true, correct, and complete.

Emory Budzinski
Senior Product Manager