

Weather Shield Series™

Elevation Details

Inswing Fixed Sidelites (6510)

Unit Dimension	1'-5 7/32"	1'-7 7/32"	1'-9 7/32"	1'-11 7/32"
Jamb Dimension	1'-2 15/32"	1'-4 15/32"	1'-6 15/32"	1'-8 15/32"
Rough Opening	1'-3 1/4"	1'-5 1/4"	1'-7 1/4"	1'-9 1/4"
Metric R.O. (mm)	387	437	488	539
Glass Size	8"	10"	12"	14"

6'-8 29/32"				
6'-7 17/32"				
6'-8"				
2032				
64 13/16"				
6'-11 13/32"				
6'-10 1/32"				
6'-10 1/2"				
2096				
67 5/16"				
7'-3 13/32"				
7'-2 1/32"				
7'-2 1/2"				
2197				
71 5/16"				
8'-1 13/32"				
8'-0 1/32"				
8'-0 1/2"				
2451				
81 5/16"				
8'-3 13/32"				
8'-2 1/32"				
8'-2 1/2"				
2502				
83 5/16"				
9'-1 13/32"				
9'-0 1/32"				
9'-0 1/2"				
2756				
90 13/16"				
10'-1 13/32"				
10'-0 1/32"				
10'-0 1/2"				
3061				
102 13/16"				

Outswing Fixed Sidelites (6610)

Unit Dimension	1'-5 21/32"	1'-7 21/32"	1'-9 21/32"	1'-11 21/32"
Jamb Dimension	1'-2 15/32"	1'-4 15/32"	1'-6 15/32"	1'-8 15/32"
Rough Opening	1'-3 1/4"	1'-5 1/4"	1'-7 1/4"	1'-9 1/4"
Metric R.O. (mm)	387	437	488	539
Glass Size	8"	10"	12"	14"

6'-9 1/8"				
6'-7 17/32"				
6'-9"				
2032				
64 13/16"				
6'-11 5/8"				
6'-10 1/32"				
6'-10 1/2"				
2096				
67 5/16"				
7'-3 5/8"				
7'-2 1/32"				
7'-2 1/2"				
2197				
71 5/16"				
8'-1 5/8"				
8'-0 1/32"				
8'-0 1/2"				
2451				
81 5/16"				
8'-3 5/8"				
8'-2 1/32"				
8'-2 1/2"				
2502				
83 5/16"				
9'-1 5/8"				
9'-0 1/32"				
9'-0 1/2"				
2756				
90 13/16"				
10'-1 5/8"				
10'-0 1/32"				
10'-0 1/2"				
3061				
102 13/16"				