

Thermal Performance Data

Contemporary Flush Frame Casement Windows - Operating (8216)

WEATHER SHIELD.

WINDOWS & DOORS

US Qualification Criteria		Climate Zone	U-Value	SHGC		
	<ul style="list-style-type: none"> ■ Northern ■ North-Central ■ South-Central ■ Southern 	Northern	<=0.22	>=0.17	Prescriptive	
			=0.23	>=0.35	Equivalent Energy Performance	
			=0.24			
			=0.25			
			=0.26			
		North-Central	<=0.25	<=0.40		
		South-Central	<=0.28	<=0.23		
		Southern	<=0.32	<=0.23		

Energy Star Version 7.0 Starting October 2023

Canadian Qualification Criteria	U-Value	or	Energy Rating
	<=1.22		>=34
Air Leakage <= 1.5 L/s/m ²			

Energy Star Version 5.0 starting January 2020

U-Value

A measurement of how much energy a material conducts. The lower the U-Value, the greater the insulating effect.

Solar Heat Gain Coefficient (SHGC)

Measures how well a window or door prevents heat from passing through it.
The lower a window or door's SHGC, the less heat it allows to pass through it.

Visible Light Transmittance

The amount of light in the visible portion of the spectrum that passes through a glazing material.

Condensation Resistance Rating

Measures how well a window resists the formation of condensation on the inside surface.
The higher the number the better resistance to condensation.

Energy Rating

A value demonstrating the balance between U-Value, SHGC and air leakage.
The higher the number, the more efficient the product.

R-Value

A measurement of how much a material resists heat transfer.
A higher R-Value means a greater insulating effect and a lower rate of heat flow out of the home.
While **R-value** measures resistance to heat transfer, **U-value** measures the rate of heat transfer.
In simple terms, **U-value** is the mathematical reciprocal of **R-value**; that is, **U = 1/R** and **R = 1/U**.

^a Total Unit calculations are derived from computer simulations that are then verified by 3rd party testing in accordance with NFRC 100, NFRC 200, and NFRC 500.

^b Published values reflect 3mm glass lite thicknesses.

ENERGY PERFORMANCE DATA									CANADIAN ENERGY PERFORMANCE DATA				CANADA ENERGY STAR v 5.0		
Contemporary Flush Frame Casement Windows - Operating (8216)								US ENERGY STAR V 7.0							
Grille Option	Glazing thickness	^NFRC Total Unit Calculations ^Glazing Option		CPD #	U-Value	Solar Heat Gain Coefficient	Visible Light Transmittance	Condensation Resistance Rating	U-Value (metric)	Maximum Air Leakage L/s/m ²	Air Infiltration/Exfiltration Average	Energy Rating			
No GIA or SDL	3/4"	Clear Insul	WEA-N-286-01214-00001	0.45	0.54	0.56	45		2.56	1.5	0.05	15			
	3/4"	Insul Low-E	WEA-N-286-01215-00001	0.33	0.29	0.49	54		1.87	1.5	0.05	16			
	3/4"	Insul Low E w/Argon	WEA-N-286-01223-00001	0.30	0.29	0.49	57		1.70	1.5	0.05	19			
	3/4"	Passive Solar	WEA-N-286-01218-00001	0.34	0.47	0.54	53		1.93	1.5	0.05	25			
	3/4"	Passive Solar w/Argon	WEA-N-286-01226-00001	0.31	0.48	0.54	56		1.76	1.5	0.05	29			
	3/4"	Passive Solar Extreme	WEA-N-286-01219-00001	0.29	0.43	0.53	41		1.65	1.5	0.05	29			
	3/4"	Passive Solar Extreme w/Argon	WEA-N-286-01227-00001	0.27	0.43	0.53	44		1.53	1.5	0.05	31			
	3/4"	Zo-e-shield 5	WEA-N-286-01216-00001	0.33	0.20	0.44	54		1.87	1.5	0.05	11			
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-286-01224-00001	0.30	0.19	0.44	57		Y	1.70	1.5	0.05	14		
	3/4"	Zo-e-shield 5 Extreme	WEA-N-286-01217-00001	0.28	0.19	0.43	42		Y	1.59	1.5	0.05	16		
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-286-01225-00001	0.26	0.19	0.43	45		Y	1.48	1.5	0.05	18		
	1"	Zo-e-shield 6	WEA-N-286-01296-00001	0.33	0.19	0.44	54			1.87	1.5	0.05	10		
	1"	Zo-e-shield 6 w/ Argon	WEA-N-286-01304-00001	0.30	0.19	0.44	57		Y	1.70	1.5	0.05	14		
	1"	Zo-e SafeGuard Certified	WEA-N-286-01301-00001	0.32	0.19	0.43	55		Y	1.82	1.5	0.05	11		
	1"	Zo-e SafeGuard Certified w/ Argon	WEA-N-286-01309-00001	0.29	0.19	0.43	58		Y	1.65	1.5	0.05	15		
	1"	Zo-e-shield 7	WEA-N-286-01252-00001	0.27	0.18	0.35	63		Y	1.53	1.5	0.05	17		
	1"	Zo-e-shield 7 w/ Argon	WEA-N-286-01264-00001	0.24	0.18	0.35	66		Y	1.36	1.5	0.05	21		
	3/4"	Insul Low-E 240	WEA-N-286-01220-00001	0.34	0.18	0.27	53			1.93	1.5	0.05	8		
	3/4"	Insul Low-E 240 w/Argon	WEA-N-286-01228-00001	0.31	0.18	0.27	56		Y	1.76	1.5	0.05	12		
	3/4"	Insul Low-E 340	WEA-N-286-01221-00001	0.33	0.13	0.27	54			1.87	1.5	0.05	6		
	3/4"	Insul Low-E 340 w/Argon	WEA-N-286-01229-00001	0.30	0.13	0.27	57		Y	1.70	1.5	0.05	10		
	3/4"	Bronze Low E	WEA-N-286-01215-00011	0.33	0.28	0.36	54			1.87	1.5	0.05	15		
	3/4"	Bronze Low E w/Argon	WEA-N-286-01223-00011	0.30	0.28	0.36	57			1.70	1.5	0.05	19		
Less Than 1" GIA or SDL	3/4"	Clear Insul	WEA-N-286-01214-00002	0.45	0.49	0.51	45			2.56	1.5	0.05	12		
	3/4"	Insul Low-E	WEA-N-286-01215-00002	0.33	0.27	0.44	54			1.87	1.5	0.05	15		
	3/4"	Insul Low E w/Argon	WEA-N-286-01223-00002	0.30	0.26	0.44	57			1.70	1.5	0.05	18		
	3/4"	Passive Solar	WEA-N-286-01218-00002	0.34	0.43	0.49	53			1.93	1.5	0.05	22		
	3/4"	Passive Solar w/Argon	WEA-N-286-01226-00002	0.31	0.43	0.49	56			1.76	1.5	0.05	26		
	3/4"	Passive Solar Extreme	WEA-N-286-01219-00002	0.29	0.39	0.48	41			1.65	1.5	0.05	26		
	3/4"	Passive Solar Extreme w/Argon	WEA-N-286-01227-00002	0.27	0.39	0.48	44			1.53	1.5	0.05	29		
	3/4"	Zo-e-shield 5	WEA-N-286-01216-00002	0.33	0.18	0.40	54			1.87	1.5	0.05	9		
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-286-01224-00002	0.30	0.18	0.40	57		Y	1.70	1.5	0.05	13		
	3/4"	Zo-e-shield 5 Extreme	WEA-N-286-01217-00002	0.28	0.18	0.39	42		Y	1.59	1.5	0.05	15		
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-286-01225-00002	0.26	0.17	0.39	45		Y	1.48	1.5	0.05	17		
	1"	Zo-e-shield 6	WEA-N-286-01296-00002	0.33	0.18	0.39	54			1.87	1.5	0.05	9		
	1"	Zo-e-shield 6 w/ Argon	WEA-N-286-01304-00002	0.30	0.18	0.39	57		Y	1.70	1.5	0.05	13		
	1"	Zo-e SafeGuard Certified	WEA-N-286-01301-00002	0.32	0.18	0.39	55		Y	1.82	1.5	0.05	10		
	1"	Zo-e SafeGuard Certified w/ Argon	WEA-N-286-01309-00002	0.29	0.17	0.39	58		Y	1.65	1.5	0.05	14		
	1"	Zo-e-shield 7	WEA-N-286-01253-00001	0.27	0.16	0.32	63		Y	1.53	1.5	0.05	16		
	1"	Zo-e-shield 7 w/ Argon	WEA-N-286-01265-00001	0.24	0.16	0.32	66		Y	1.36	1.5	0.05	19		
	3/4"	Insul Low-E 240	WEA-N-286-01220-00002	0.34	0.17	0.25	53			1.93	1.5	0.05	7		
	3/4"	Insul Low-E 240 w/Argon	WEA-N-286-01228-00002	0.31	0.16	0.25	56		Y	1.76	1.5	0.05	11		
	3/4"	Insul Low-E 340	WEA-N-286-01221-00002	0.33	0.12	0.24	54			1.87	1.5	0.05	6		
	3/4"	Insul Low-E 340 w/Argon	WEA-N-286-01229-00002	0.30	0.12	0.24	57		Y	1.70	1.5	0.05	10		
	3/4"	Bronze Low E	WEA-N-286-01215-00012	0.33	0.25	0.33	54			1.87	1.5	0.05	13		
	3/4"	Bronze Low E w/Argon	WEA-N-286-01223-00012	0.30	0.25	0.33	57			1.70	1.5	0.05	17		
1" Or Over GIA or SDL	3/4"	Clear Insul	WEA-N-286-01214-00003	0.45	0.44	0.46	45			2.56	1.5	0.05	9		
	3/4"	Insul Low-E	WEA-N-286-01215-00003	0.33	0.24	0.40	54			1.87	1.5	0.05	13		
	3/4"	Insul Low E w/Argon	WEA-N-286-01223-00003	0.30	0.24	0.40	57			1.70	1.5	0.05	17		
	3/4"	Passive Solar	WEA-N-286-01218-00003	0.34	0.39	0.44	53			1.93	1.5	0.05	20		
	3/4"	Passive Solar w/Argon	WEA-N-286-01226-00003	0.31	0.39	0.44	56			1.76	1.5	0.05	24		
	3/4"	Passive Solar Extreme	WEA-N-286-01219-00003	0.29	0.36	0.43	41			1.65	1.5	0.05	25		
	3/4"	Passive Solar Extreme w/Argon	WEA-N-286-01227-00003	0.27	0.36	0.43	44			1.53	1.5	0.05	27		
	3/4"	Zo-e-shield 5	WEA-N-286-01216-00003	0.33	0.16	0.36	54			1.87	1.5	0.05	8		
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-286-01224-00003	0.30	0.16	0.36	57		Y	1.70	1.5	0.05	12		
	3/4"	Zo-e-shield 5 Extreme	WEA-N-286-01217-00003	0.28	0.16	0.35	42		Y	1.59	1.5	0.05	14		
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-286-01225-00003	0.26	0.16	0.35	45		Y	1.48	1.5	0.05	17		
	1"	Zo-e-shield 6	WEA-N-286-01296-00003	0.33	0.16	0.36	54			1.87	1.5	0.05	8		
	1"	Zo-e-shield 6 w/ Argon	WEA-N-286-01304-00003	0.30	0.16	0.36	57		Y	1.70	1.5	0.05	12		
	1"	Zo-e SafeGuard Certified	WEA-N-286-01301-00003	0.32	0.16	0.35	55		Y	1.82	1.5	0.05	9		
	1"	Zo-e SafeGuard Certified w/ Argon	WEA-N-286-01309-00003	0.29	0.16	0.35	58		Y	1.65	1.5	0.05	13		
	1"	Zo-e-shield 7	WEA-N-286-01253-00002	0.27	0.15	0.29	63		Y	1.53	1.5	0.05	15		
	1"	Zo-e-shield 7 w/ Argon	WEA-N-286-01265-00002	0.24	0.15	0.29	66		Y	1.36	1.5	0.05	19		
	3/4"	Insul Low-E 240	WEA-N-286-01220-00003	0.34	0.15	0.22	53			1.93	1.5	0.05	6		
	3/4"	Insul Low-E 240 w/Argon	WEA-N-286-01228-00003	0.31	0.15	0.22	56		Y	1.76	1.5	0.05	10		
	3/4"	Insul Low-E 340	WEA-N-286-01221-00003	0.33	0.11	0.22	54			1.87	1.5	0.05	5		
	3/4"	Insul Low-E 340 w/Argon	WEA-N-286-01229-00003	0.30	0.11	0.22	57		Y	1.70	1.5	0.05	9		
	3/4"	Bronze Low E	WEA-N-286-01215-00013	0.33	0.23	0.30									