

Contemporary Collection™

Elevation Details

French Casement Windows (8218) - Shadowline Frame (8221) - Flush Frame
 Push-Out French Casements (8217) - Shadowline Frame (8220) - Flush Frame

Jamb Dimension	3'-3 1/16"	3'-11 1/16"	4'-7 1/16"	4'-11 1/16"	5'-3 1/16"	5'-11 1/16"
Rough Opening	3'-3 9/16"	3'-11 9/16"	4'-7 9/16"	4'-11 9/16"	5'-3 9/16"	5'-11 9/16"
Metric R.O. (mm)	1005	1208	1411	1513	1614	1818
Glass Size	15 3/16"	19 3/16"	23 3/16"	25 3/16"	27 3/16"	31 3/16"
2'-11 1/2"						
3'-0"						
3'-5 1/2"						
3'-6"						
3'-11 1/2"						
4'-0"						
4'-5 1/2"						
4'-6"						
4'-11 1/2"						
5'-0"						
5'-5 1/2"						
5'-6"						
5'-11 1/2"						
6'-0"						
6'-5 1/2"						
6'-6"						
6'-11 1/2"						
7'-0"						

Shaded units meet or exceed egress opening requirements per 2015 IBC (International Building Code) minimum dimensions of 20" [508mm] clear opening width, 24" [610mm] clear opening height, 5.7 sq. ft. [5295cm²] clear opening and floor to bottom of clear opening not to exceed 44" [1118mm] in height.

Verify local or state egress opening sizes with your local building inspector.

Floor to bottom of clear opening dimensions are based on 82" [2083mm] jamb height of Weather Shield French doors and center hinged French doors.

See Opening Specification chart for reference.

NOTE: 66 & 70 heights available for Push-out only